

## WHAT PROPERTY OWNERS LOVE

LESS OVERHEAD SPACE NEEDED

does not hinder lighting or overhead storage

**MINIMAL MAINTENANCE** apply light oil to springs, bushings and guides

**LOCK OPTIONS** outside mounted pad lock hasp or inside box lock.

CLIMATE CONTROL OPTIONS a blanket of reflective double bubble insulation protects your interior. Seal off outdoor elements with a weather brush.

## **SPECS YOU NEED**

**EASIER INSTALLATION** means lower labor costs.

**REFLECTIVE DOUBLE BUBBLE INSULATION** glues to the curtain interior.

**WEATHER BRUSH** polypropylene strip of filaments fitted in an aluminum retainer mounted to the door jamb which conforms to the corrugated surface of the door.

**SOLID STEEL DOOR CURTAIN** cold roll formed 26 gauge high grade galvanized steel coated in polyester paint. Panels are assembled and lock seamed to form a solid steel curtain.

**BOTTOM EDGE** extruded aluminum that includes a blade style gasket seal.

**GUIDES** extruded aluminum that includes a plastic wear strip to buffer door curtain.

ROLLER DRUM 1" schedule 40 pipe with welded steel drums. Factory installed helical wound springs counter balance the weight of the door curtain.

**SUPPORT BRACKETS** 12 guage galvanized steel with heavy bushings to carry roller drum.

## **CLEARANCES**:

Side room required: 5.5" Head room required: 14" for up to 8' high doors / 16" for up to 10' high doors

## 2 YEAR WARRANTY

We promise your door is free of defects in craftmanship and materials for 2 years from your date of purchase.