



For doors up to 14' wide x 14' high

# MODEL 200

EXCELLENT FOR SERVICE DOORS

Easy Installation • Low Maintenance  
Easy Operation • 7 Curtain Color Choices  
Motor or Chain Hoist Operation

## WHAT PROPERTY OWNERS LOVE

### **LESS OVERHEAD SPACE NEEDED**

does not hinder lighting or overhead storage

**MINIMAL MAINTENANCE** apply light oil to springs, bushings and guides

**OPERATION OPTIONS** can be motor, push up, or chain hoist operated.

**LOCK OPTIONS** outside mounted pad lock hasp or inside box lock.

**CLIMATE CONTROL OPTIONS** a blanket of reflective double bubble insulation protects your interior. Seal off outdoor elements with a weather brush.

## SPECS YOU NEED

**EASIER INSTALLATION** means lower labor costs.

**REFLECTIVE DOUBLE BUBBLE INSULATION** glues to the curtain interior.

**WEATHER BRUSH** polypropylene strip of filaments fitted in an aluminum retainer mounted to the door jamb which conforms to the corrugated surface of the door.

**SOLID STEEL DOOR CURTAIN** cold roll formed 26 gauge high grade galvanized steel coated in polyester paint. Panels are assembled and lock seamed to form a solid steel curtain.

**BOTTOM EDGE** extruded aluminum that includes a blade style gasket seal.

**GUIDES** extruded aluminum and a vinyl wear strip to buffer door curtain movement.

**ROLLER DRUM** 1.25" schedule 40 pipe with welded steel drums. Factory installed helical wound springs counter balance the weight of the door curtain.

**SUPPORT BRACKETS** 12 guage galvanized steel with heavy bushings to carry roller drum.

### **CLEARANCES:**

Side room required: 7.5" for push up operation, 11.5" reduced drive chain hoist operation and 20" for electric motor operation

Head room required: 19" up to 10' high / 22" up to 14' high

## 2 YEAR WARRANTY

We promise your door is free of defects in craftsmanship and materials for 2 years from your date of purchase.