Call for your custom quote 425-259-6559 · rollrightdoors.com



Easy Installation • Low Maintenance • Easy Operation White or Galvanized Curtain Finish Motor or Chain Hoist Operation Vision or Ventilation Slots Available

WHAT PROPERTY OWNERS LOVE

LESS OVERHEAD SPACE NEEDED does not hinder lighting or overhead storage

MINIMAL MAINTENANCE apply light oil to springs, bushings and guides **OPERATION OPTIONS** standard chain hoist operated or can be motor operated.

OPTIONAL HOODS

SPECS YOU NEED

EASIER INSTALLATION means lower labor costs.

DOOR CURTAIN cold rolled 24 gauge high grade galvanized or prime painted steel slats with cast iron end locks.

Bottom is constructed of 2 – 1.5" galvanized steel angles bolted back to back on bottom slat with tubular bottom seal

GUIDES cold roll formed 14 gauge galvanized steel mounted to structural wall angles.

SUPPORT BRACKETS .25" steel plate fabricated to accept shaft roller bearings and hood.

POWERMASTER MOTORS sized per door based on weight and usage.

CHAIN HOIST cast iron drive and driven gear assembly pre – installed

CLEARANCES:

Side room required: 6.5" Head room required: 16" up to 14' high / 18" up to 18' high

2 YEAR WARRANTY

We promise your door is free of defects in craftmanship and materials for 2 years from your date of purchase.