Designed for use on commercial sectional doors with high or vertical lift track and small rolling doors, shutters and grilles that require no more than 15 cycles per hour

STANDARD FEATURES

- 2 year Warranty
- 24V class 2 control circuit with 40VA transformer to protect against short circuit
- On board receiver with antenna
- External radio control terminal strip
- Low friction powder metal limit cam nuts with fully adjustable rotary type limit switch assembly
- Three button open-close-stop control station Nema-1
- \bullet 1/2 HP high starting torque, instant reversible motor protected by internal automatic thermal overload device
- Motor removable without affecting limit settings
- Heavy duty worm gear reduction in oil bath gearbox
- #41 roller chain drive & 41B19 operator drive sprocket standard
- Emergency floor level disconnect for manual operation
- Manual override drive device for jammed doors
- Chain keeper
- Left or right hand mounting (must specify at time of order)
- #41 roller chain and sprockets on final drive
- Patented Mechanical Load Sensing feature (optional) will detect a locked or jammed door and stop unit from operation
- Baked on dark grey coat finish
- Shipping weight 55 lbs
- N-1 photocells included for doors up to 24' wide



When ordering a PRO-GJ operator, supply Nice with the following information:

- Door height
- Door width
- Type of door
- Horsepower
- Voltage/ Phase
- Safety devices
- Door shaft diameter & door shaft key size
- Mounting (LH or RH, Bracket or Wall mount)
- Control circuit options (see page 5-6)





